

CHICAGO TRANSIT AUTHORITY

RAPID TRANSIT SYSTEM

APRIL 1, 1970

MOTOR CARS

NO. OF CARS	CAR NOS.	BUILDER	YEAR	WEIGHT	SEATS "A" "B"	MOTORS			CONTROL				REMARKS
						NO. OF AND TYPE	% FIELD SHUNTING	H.P.	MFG	TYPE	*	**	
2	1-2	St. Louis	1960	54,140	46	4GE1250K1	65	100	GE	SPM	A	PT	Double End-Conversion - High Speed
1	3	St. Louis	1960	53,000	46	4WH1454J	64	100	WH	WCC-440	B	T	Double End-Conversion - High Speed
1	4	St. Louis	1960	50,000	46	4WH1454J	S69,P47	100	WH	XDA-152	X	T	Double End-Conversion - High Speed
18	5-22	St. Louis	1959	45,100	46	4GE1220F1	50	55	WH	XDA-1G	X	-	Double End-Conversion
4	23-26	St. Louis	1959	46,500	46	4WH1432LK	63	55	WH	XDA-1G	X	PT	Double End-Conversion
2	27-28	St. Louis	1959	46,000	46	4GE1220F1	50	55	WH	XDA-1G	X	T	Double End-Conversion
2	29-30	St. Louis	1959	46,500	46	4WH1432LK	63	55	WH	XDA-1G	W	PT	Double End-Conversion
8	31-38	St. Louis	1959	44,800	46	4GE1220F1	50	55	WH	XDA-52	X	-	Double End-Conversion
12	39-50	St. Louis	1959	45,900	46	4GE1220F1	50	55	WH	XDA-1G	X	T	Double End-Conversion
2	51-52	Pullman	1947	93,800	96	8WH1432LK	60	55	WH	XDA-1	W	PT	Articulated 3 Section
2	53-54	St. Louis	1948	91,700	96	8WH1432LK	50	55	WH	XDA-1A	W	PT	Articulated 3 Section
180	2001-2180	Pullman	1964	47,400	47-51	4GE1250K1	45	100	GE	SCM	Z	-	Fluorescent Lights-Air Conditioned
128	2201-2350	Budd	1969-70	45,000	47-51	4GE1250K1	40	100	GE	SCM	Z	-	Fluorescent Lights-Air Cond. Aluminum Centered Wheels
15	4067-4250	Cincinnati	1914-16	70,000	52	2WH567-R1	#	160	WH	264-S	Y	-	
188	4251-4455	Cincinnati	1922-25	76,800	52	2WH567-R1	#	160	WH	480-T	Y	T	
126	6001-6126	St. Louis	1950-51	41,700	47-51	4WH1432LK	50	55	WH	XDA-1A	X	-	New
1	6127	St. Louis	1951	45,700	47	4WH1452A	S60,P40	100	WH	XDA-2	X	T	High Speed-Fluorescent Lights - New
1	6128	St. Louis	1951	49,100	51	4GE1250U1	S60,P40	100	WH	XDA-2	X	T	High Speed-Fluorescent Lights - New
2	6129-6130	St. Louis	1951	42,900	47-51	4GE1247A1	S68	100	GE	SCM	X	T	Fluorescent Lights - New
70	6131-6200	St. Louis	1951	41,700	47-51	4WH1432LK	50	55	WH	XDA-1A	X	-	New
266	6201-6470	St. Louis	1954-55	42,700	50	4WH1432LK	50	55	WH	XDA-1D	X	-	Conversion-Conductor's Cab
12	6471-6482	St. Louis	1956	41,250	47-51	4WH1432LK	50	55	WH	XDA-1D	X	-	Conversion
28	6483-6510	St. Louis	1956	41,250	47-51	4GE1220F1	50	55	WH	XDA-1D	X	-	Conversion
210	6511-6720	St. Louis	1957-59	44,350	47-51	4GE1220F1	50	55	WH	XDA-1L	X	-	Conversion *
2	6721-6722	St. Louis	1954-55	42,700	47-51	4GE1220F1	50	55	WH	XDA-1D	X	-	Conversion
1283	TOTAL												

* - Combinations which may be trained together

** - (T - Cars equipped for trolley operation

*** - (PT - Automatic pan trolley for Skokie operation

Car 24 equipped with pantograph

- Field Tapped

+ - 6711 Air Conditioned Total Car Weight 46,800

CHICAGO TRANSIT AUTHORITY

RAPID TRANSIT SYSTEM

APRIL 1, 1970

RAPID TRANSIT EQUIPMENT DATA

NO. OF CARS	CAR NOS.	TRUCK	TRUCK WEIGHT	WHEEL DIA.	GEAR ASSEMBLY		DRIVE SHAFT	FRICTION BRAKE	TRACK BRAKE
					MODEL	RATIO			
2	1-2	LFM-CTA #1	23,000	28"	GL 7GA47C1	6.125:1	28-29/32"	ASF Simplex	4
1	3	LFM-CTA #2	22,800	28"	WGB-75-1	5.88:1	None	Westinghouse Electro-Hydraulic	4
1	4	LFM-CTA #2	22,600	28"	WG-75-1	5.88:1	None	Warner Electric	4
18	5-22	St. Louis B-3	18,100	26"	B-3	7.17:1	28"	Wabco A-2	4
4	23-26	St. Louis B-3	18,300	26"	B-3	7.17:1	28"	Wabco A-2	4
2	27-28	St. Louis B-3	18,100	26"	B-3	7.17:1	28"	Wabco A-2	4
2	29-30	St. Louis B-3	18,300	26"	B-3	7.17:1	28"	Wabco A-2	4
20	31-50	St. Louis B-3	18,100	26"	B-3	7.17:1	28"	Wabco A-2	4
2	51-52	Clark Special	37,500	28"	Clark Special	7.17:1	26-5/8"	Clark	8
2	53-54	St. Louis B-4	37,500	28"	St. Louis B-4	6.125:1	28"	Wabco A-2	8
180	2001-2180	LFM-CTA #1	22,950	28"	GL 7GA47C1	6.125:1	28-29/32"	ASF Simplex	4
128	2201-2350	Budd Pioneer 3	10,250	28"	GL 7GA47C2	6.125:1	24-3/4"	ASF Simplex	4
203	4067-4455	#1 Baldwin 78"	22,300	34"	Gear Pan	60/17	None	Air Tread	None
	4067-4455	#2 Baldwin 66"	9,300	31"	None	None	None	Air Tread	None
126	6001-6126	Clark B-2	17,200	26"	B-2	7.17:1	28"	Clark	2
1	6 6127	Prototype LFM-CTA #1	20,700	28"	Dana 7-7	5.88:1	28"	ASF	None
1	6128	St. Louis B-20	24,100	28"	GL 7GA42	6.125:1	27-9/16"	ASF	4
2	6129-6130	Clark B-2	18,400	26"	B-2	7.17:1	28"	Clark	2
70	6131-6200	Clark B-2	17,200	26"	B-2	7.17:1	28"	Clark	2
306	6201-6510	Clark B-2	16,900	26"	B-2	7.17:1	28"	Clark	2
210	6511-6720	St. Louis B-3	18,100	26"	B-3	7.17:1	28"	Wabco A-2	4
2	6721-6722	Clark B-2	16,900	26"	B-2	7.17:1	28"	Clark	2
1283	TOTAL								

CHICAGO TRANSIT AUTHORITY
SHOPS AND EQUIPMENT DEPARTMENT

APRIL 1, 1970

MOTOR BUS DATA SHEET

No. of Buses	Series	Series Code	Mfr. & Model No.	Year Received	Length (Inches)	Width (Inches)	Weight (Pounds)	Seating Capacity	Fuel		Governor Speed (MPH)	Axle Ratio	Tire Size	Steering
									Type	Tank Capacity				
150	100- 249	01	GM-TDH5301	1961	479	101-3/4	20,400	50	D	86	45-50	5-1/7 to 1	11.00 x 20	Power
150	300- 449	03	GM-TDH5301	1962-3	480-1/2	101-3/4	20,700	50	D	86	45-50	5-1/7 to 1	11.00 x 20	Power
93	601- 700	05	GM-TDH5103	1950-1	477	103-1/2	19,100	51	D	82	45-50	5-1/6 to 1	11.00 x 20	Manual
**5	800- 804	08	GM-TDH5303	1965	480-1/2	101-3/4	21,870	50	D	120	60-65	4.11 to 1	11.00 x 20	Power
237	3000-3238	30	FLX F2D6V401-1	1965	483-1/8	102	21,230	50	D	86	45-50	5-4/7 to 1	11.00 x 20	Power
1	3239	30	FLX F2DV8C401-1	1965	483-1/8	102	21,590	50	D	120	45-50	4-5/8 to 1	11.00 x 20	Power
**5	3240-3244	32	FLX F2D6V401-1	1965	483-1/8	102	23,520	50	D	120	60-65	4.00-5.51	11.00 x 20	Power
150	3300-3449	33	FLX F2D6V351-1	1966	421-15/16	102	20,158	42	D	125	45-50	5.57 to 1	*12.00 x 22.5	Power
195	3500-3694	35	FLX F2D6V401-1	1966-7	482-7/8	102	21,030	50	D	125	45-50	5-4/7 to 1	*12.00 x 22.5	Power
5	3695-3699	35	FLX F2DV8C401-1	1967	482-7/8	102	21,030	50	D	125	65	4-5/8 to 1	*12.00 x 22.5	Power
30	3700-3729	37	FLX FD6VT401-1	1969	480-15/16	96	20,440	50	D	125	45-50	5-1/7 to 1	*12.00 x 22.5	Power
146	3730-3875	37	FLX F2D6VT401-1	1968-9	480-15/16	102	20,694	50	D	125	45-50	5-1/7 to 1	*12.00 x 22.5	Power
334	5000-5499	50	TWIN 52S2P	1950-1	482	102	18,500	51	P	104	45-50	6-5/6 to 1	11.00 x 20	Manual
491	5500-5999	55	TWIN FT2P-40	1953-4-5	480	102	21,057	50	P	104	45-50	6-5/6 to 1	11.00 x 20	Manual
81	7200-7299	72	MACK C-49PGT	1956-7	473-1/2	102	22,975	49	P	125	45-50	5-3/8 to 1	11.00 x 20	Power
150	8000-8149	80	TWIN FT2P-40	1956-7	480	102	21,310	50	P	125	45-50	6-5/6 to 1	11.00 x 20	Manual
150	8200-8349	82	TWIN FT2P-40	1958-9	480	102	21,750	50	P	125	45-50	6-5/6 to 1	11.00 x 20	Power
99	8400-8498	84	TWIN FT2P-35	1959	421-3/4	102	20,780	44	P	125	45-50	6-5/6 to 1	11.00 x 20	Power
1	8499	84	TWIN F2DD-40	1960	480	102	23,060	48	D	120	45-50	5-4/7 to 1	11.00 x 20	Power
100	8500-8599	85	TWIN F2D6V401	1961	483	102	21,300	50	D	85	45-50	5-4/7 to 1	11.00 x 20	Power
51	8600-8650	85	TWIN F2D6V401	1961-2	483	102	21,300	50	D	85	45-50	5-4/7 to 1	11.00 x 20	Power
149	8700-8848	87	FLX F2P-401	1963	483-1/8	102	21,130	50	P	141	45-50	6-5/6 to 1	*12.00 x 22.5	Power
1	8849	87	FLX F2P-401	1963	483-1/8	102	22,000	50	P	141	45-50	5-4/7 to 1	*12.00 x 22.5	Power
2774	TOTAL	1455 Propane Buses 1319 Diesel Buses												

* TUBELESS TYPE

**These buses are Air Conditioned.

TROLLEY BUS DATA SHEET

No. of Buses	Series	Series Code	Mfr.	Year Received	Length (Inches)	Width (Inches)	Weight (Pounds)	Seating Capacity	Motor Mfr. and Number	Rear Axle Ratio	Tire Size	Control Mfr.
315	9413-9761	94	Marmon-Harrington	1951-2	478-5/8	102	20,340	49	GE-1213J3	11.58:1	11.00 x 22	MRC

CHICAGO TRANSIT AUTHORITY
SHOPS AND EQUIPMENT DEPARTMENT

APRIL 1, 1970

MOTOR BUS DATA SHEET

No. of Buses	Series	Series Code	ENGINE DATA				TRANSMISSION		CHARGING SYSTEM			Suspension
			Mfrgr. & Model No.	Horsepower RPM	Displacement	Compression Ratio	Mfrgr.	Model No.	Type	Mfrgr.	Output	
150	100- 249	01	GM-6V-71	190 @ 2000	425.6 cu. in.	17.0 to 1	Allison	VH	Alternator	Delco Remy	220A	Air Ride
150	300- 449	03	GM-6V-71	183 @ 2000	425.6 cu. in.	17.0 to 1	Allison	VH	Alternator	Delco Remy	220A	Air Ride
93	601- 700	05	GM-671	200	425.6 cu. in.	16.0 to 1	Allison	V DR.	Generator	Delco Remy	120A	Spring
**5	800- 804	08	6V-71	197 @ 2000	425.6 cu. in.	17.0 to 1	Allison	VH	Alternator	Delco Remy	300	Air Ride
237	3000-3238	30	GM-6V-71	175 @ 2150	425.6 cu. in.	17.0 to 1	Spicer	184-1A	Alternator	Delco Remy	300	Air Ride
1	3239	30	Cummins V8-E235	210 @ 2500	785.0 cu. in.	15.7 to 1	Spicer	184-1A	Alternator	Delco Remy	300	Air Ride
**5	3240-3244	32	GM-6V-71	211 @ 2100	425.6 cu. in.	17.0 to 1	Spicer	184-1B	Alternator	Delco Remy	300	Air Ride
150	3300-3449	33	GM-6V-71N	176 @ 2100	425.6 cu. in.	18.7 to 1	Spicer	184	Alternator	Delco Remy	300	Air Ride
195	3500-3694	35	GM-6V-71N	176 @ 2100	425.6 cu. in.	18.7 to 1	Spicer	184	Alternator	Delco Remy	300	Air Ride
5	3695-3699	35	Cummins V8-E235	210 @ 2500	785.0 cu. in.	16.3 to 1	Spicer	184	Alternator	Delco Remy	300	Air Ride
30	3700-3729	37	DD-6V-71N	173 @ 2000	425.6 cu. in.	18.7 to 1	Allison	VH	Alternator	Delco Remy	300	Air Ride
146	3730-3875	37	DD-6V-71N	173 @ 2000	425.6 cu. in.	18.7 to 1	Allison	VH	Alternator	Delco Remy	300	Air Ride
334	5000-5499	50	FTC-200-3	200 @ 2800	451.0 cu. in.	*	Spicer	916	Generator #	Delco Remy	120	Torsilastic
491	5500-5999	55	FTC-200-45	200 @ 2800	451.0 cu. in.	*	Spicer	918	Alternator	Leece Neville	100	Torsilastic
81	7200-7299	72	EN-510A	175 @ 2400	510.0 cu. in.	9.48 to 1	Spicer	183	Generator	Delco Remy	120	Air Ride
150	8000-8149	80	FTC-200-63	200 @ 2800	451.0 cu. in.	*	Spicer	183	Alternator	Leece Neville	100	Torsilastic
150	8200-8349	82	FTC-200-65	200 @ 2800	451.0 cu. in.	*	Spicer	183	Alternator	Leece Neville	100	Air Ride
99	8400-8498	84	FTC-200-67	200 @ 2800	451.0 cu. in.	*	Spicer	183	Alternator	Leece Neville	100	Air Ride
1	8499	84	DD-6V-71	210 @ 2100	425.6 cu. in.	17.0 to 1	Spicer	184	Alternator	Delco Remy	220	Air Ride
100	8500-8599	85	DD-6V-71	190 @ 2000	425.6 cu. in.	17.0 to 1	Spicer	183	Alternator	Delco Remy	220	Air Ride
51	8600-8650	85	DD-6V-71	190 @ 2000	425.6 cu. in.	17.0 to 1	Spicer	184	Alternator	Delco Remy	220	Air Ride
149	8700-8848	87	FTC-200-69	163 @ 2400	451.0 cu. in.	*	Spicer	184	Alternator	Delco Remy	220	Air Ride
1	8849	87	GMC-V8-637	250 @ 2400	637.0 cu. in.	9.4 to 1	Spicer	184	Alternator	Delco Remy	220	Air Ride
2774	TOTAL	1455 Propane Buses 1319 Diesel Buses										

* 8.9 to 9.0 depending on cylinder head used.

** These buses are Air Conditioned.

Buses 5250 to 5499 have an alternator from Leece Neville.

TROLLEY BUS DATA SHEET

No. of Buses	Series	Series Code	Motor H.P.	Voltage D.C.	Current Rating	Brakes	Height (Poles Down)	Suspension	Steering	Rear Door
315	9413-9761	94	140	6000	194 Amps	Dynamic/Air	123-1/2"	Springs	Manual	Treadle